

Gigabit 8 SFP Ports Fiber Switch

FEATURES

- Support switch 10/100/1000Base-T and 1000Base-SX/LX
- 1.25Gbps full duplex fiber ports
- 2x1000M Ethernet port with auto-negotiation
- MDI/MDIX and half/full-duplex



SPECIFICATIONS

Model No.	FSC - 8FET-SFP
Standards	
Standards	IEEE802.3 10Base-T IEEE802.3u 100Base-TX/FX IEEE802.3ab 1000Base-T IEEE802.3z 1000Base-SX/LX IEEE802.3x Flow control IEEE802.1p QoS IEEE802.1d Spanning Tree IEEE802.3az
Ethernet Port	
Connector	RJ45
Data Rate	10/100/1000M
Distance	0~100m
UTP Type	UTP-5E or 6
Fiber Port	
Connector	SFP slot
Data Rate	1.25Gbps
Optical Wavelength	850nm/1310nm/1490nm/1550nm
Distance	550m~120km
Performance	
Processing Type	Store and Forward
MAC Table	8K
Buffer Space	1Mbit
Max. Packet Length	9K bytes
Back Bandwidth	20G
Time Delay	< 20μs

Power	
Power type	External Power Supply
Input Voltage	AC100V~240V, 5-/60Hz
Connector	DC Socket
Working Voltage	5V
Power Consumption	4W~10W
General	
Working Temperature	-10°C ~ 55°C
Working Humidity	5~90% (non-condensing)
Color	Metal, Black
Dimension	216x133x30mm
Weight	0.55kg