

FSC - IPC4120-FCI

4Mpx Network Camera H.265+ IR Dome Varifocal

FEATURES

- 0.01 Lux
- Super WDR up to 120dB
- H.265+ High Efficiency Video Coding
- Varifocal lens 2.8 - 12mm
- IR distance up to 30m
- Support Video Content Analysis (Optional)

SPECIFICATIONS

Model No.	FSC - IPC4120-FCI
Camera	
Image Sensor	4.0 Mpx, 1/2.8" Progressive Scan
WDR	Super WDR up to 120dB
Effective Pixels	Main Stream: 2680*1520@25fps SubStream : 800*448@25fps
Shutter	1/100000s ~ 1/5s
Minimum Illumination	Color: 0.01 Lux @F1.2 B/W: 0.01 Lux with IR on
Lens	2.8 - 12mm
IR Distance	30 pcs LED light, up to 30 m
Day/Night	ICR Filter Auto Switch
Video	
Max Image Resolution	2680 x 1520
Compression Format	H.265/H.264
Image Setting	Brightness/Contrast/Saturation/Sharpness
Video Bit Rate	4Mbps (CBR/VBR adjustable)
Frame Rates	Support 1 ~30fps adjustable
Primary Stream	2680 x 1520 : 25 fps



System	
Ethernet	1 x RJ45 10M/ 100M Ethernet port
Protocol	RTSP, TCP/IP, UDP, DNS, DDNS, DHCP, FTP, NTP, SMTP, UPnP, PPPoE
Event Trigger	Motion detection, Video Blind, Video Loss
System Compatibility	ONVIF
General	
Working Temperature	-10°C ~ 60°C
Working Humidity	10~90% (non-condensing)
Power Supply	DC12V/PoE (IEEE802.3af)
Power Consumption	12Vdc, 2A MAX (with IR on)
Weight	1.5kg