

## 8Mpx Network Camera H.265+ IR Mini Dome

### FEATURES

- 0.01 Lux
- Super WDR up to 120dB
- H.265+ High Efficiency Video Coding
- Built-in Microphone
- IR distance up to 30m
- Support Video Content Analysis ( Optional )



### SPECIFICATIONS

<b>Model No.</b>	<b>FSC - IPC8520-FHI</b>
<b>Camera</b>	
Image Sensor	8.0Mpx (4K), 1/2.8" Progressive Scan
WDR	Super WDR up to 120dB
Effective Pixels	Main Stream: 3840*2160@25fps SubStream : 800*448@25fps
Shutter	1/100000s ~ 1/5s
Minimum Illumination	Color: 0.01 Lux @F1.2 B/W: 0.01 Lux with IR on
Lens	3.6mm@F2.2/6mm @F1.6
IR Distance	up to 30 m
Day/Night	ICR Filter Auto Switch
<b>Video</b>	
Max Image Resolution	3840 x 2160
Compression Format	H.265/H.264
Image Setting	Brightness/Contrast/Saturation/Sharpness
Video Bit Rate	6 ~ 8Mbps ( CBR/VBR adjustable )
Frame Rates	Support 1 ~ 30fps adjustable
Primary Stream	3840 x 2160 : 25 fps
<b>Audio</b>	
Audio Input/Output	1ch input (Microphone)
Audio Compression	G.711

<b>System</b>	
Ethernet	1 x RJ45 10M/ 100M Ethernet port
Protocol	RTSP, TCP/IP, UDP, DNS, DDNS, DHCP, FTP, NTP, SMTP, UPnP, PPPoE
Event Trigger	Motion detection, Video Blind, Video Loss
System Compatibility	ONVIF
<b>General</b>	
Working Temperature	-10°C ~ 60°C
Working Humidity	10~90% (non-condensing)
Power Supply	DC12V/PoE ( IEEE802.3af )
Power Consumption	12Vdc, 2A MAX ( with IR on )
Dimension	Ø 120mm x 60mm
Weight	0.6kg