

5Mpx Network Camera

H.265+ IR Mini Dome

FSC-IPC5520-FHI



Features

- 0,01 Lux
- Super WDR up to 120dB
- H.265+ High Efficiency Video Coding
- Built-in Microphone
- IR distance up to 30m
- Support Video Content Analysis (Optional)

Specifications

Model No.	FSC-IPC5520-FHI
Camera	
Image Sensor	5.0Mpx, 1/2.8" Progressive Scan
WDR	Super WDR up to 120dB
Effective Pixels	Main Stream: 2560×1920@25fps SubStream : 800×448@25fps
Shutter	1/100000~1/5s
Minimum Illumination	Color: 0,01 Lux @F1.2 B/W: 0,01 Lux with IR on
Lens	3.6mm@F2.2/6mm @F1.6
IR Distance	Up to 30m
Day/Night	ICR Filter Auto Switch
Video	
Max Image Resolution	2560×1920
Compression Format	H.265/H.264
Image Setting	Brightness/Contrast/Saturation/Sharpness
Video Bit Rate	5Mbps (CBR/VBR adjustable)
Frame Rates	Support 1 ~30fps adjustable
Primary Stream	2560×1920@25fps
Audio	
Audio Input/Output	1 Ch input (microphone)
Audio Compression	G.711

System	
Ethernet	1 x RJ45 10M/ 100M Ethernet port
Protocol	RTSP, TCP/IP, UDP, DNS, DDNS, DHCP, FTP, NTP, SMTP, UPnP, PPPoE
Event Trigger	Motion detection, Video Blind, Video Loss
System Compatibility	ONVIF
General	
Working Temperature	-10°C~60°C
Working Humidity	10~90% (non-condensing)
Power Supply	DC 12V/PoE (IEEE802.3af)
Power Consumption	12V DC, 2A MAX (with IR on)
Dimensions	120×60mm
Weight	0,6kg